				OMB N	o. <b>06</b> 5	1-0011 (	12/31/86	5)
PATENT A	PPLICATION TE	ransmittal le	TTER		ATTOR	NEY'S DOC	KET NO.	
TO THE COMMISSIONER			7101	NASA	-0		J.S. PTO	24236
for SYSTED	and h	CTH OL	FOA (	E110	LA	R	0875	***************************************
Enclosed are:	OMNUM	( ATION 7					<u></u>	
	sheets of drawing.	710 M.	MOAD	(op	TD	MICA	Trag	,
a certified copy of a		· · · · · · · · · · · · · · · · · · ·					pplication.	
associate power of a				27 CER			-	
verified states	ment to establi	sh smail extity	status und	er 37 CFR	1.9 42	14 1.27.		
C	LAIMS AS FIL	.ED	SMALL E	NTITY		OTHER 1 SMALL I		
FOR	NO FILED	NO EXTRA	RATE	FEE	<u>or</u>	RATE	FEE	
BASIC FEE				\$ 345	OR		s	1
TOTAL CLAIMS 15	-20 -	•	x \$ =	. 0	<u>OR</u>	* \$ =	s	
INDEP CLAIMS	-3 -	•	×\$ *	10	OR	×\$ 3	\$	
MULTIPLE DEPENDENT CLAIM	A PRESENT	0	+ \$ =	: 0	<u>OR</u>	+ <b>s</b> -	3	
If the difference in col. 1 is less t	than zero lenter "O" in o	ool. 2	TOTAL	: 342	<u>OR</u>	TOTAL	\$	
Please charge A duplicate co			in	the amoun			 \$\dag{t}	Programme and pr
A check in the	amount of \$	345 to cover	r the filing	fee is encl	osed.	440 Fol	3 (2 & Cd	BIA
associated wit	h this communi	uthorized to ch cation or credit uplicate copy o	t any overpa	yment to	followi Deposi: J	ng fees t Account		To Provide the Control of the Contro
☐ Any a	dditional filing	fees required v	under 37 CF	R 1.16.	To	TPI:	287	
Amy p	atent application	on processing fe	ses under 37	CFR 1.17				  -  -
the pendency o	f this applicati	uthorized to chion or credit an plicate copy of	y overpayme	ent to Dep			ring	
Any f	iling fees unde	r 37 CFR 1.16 f	or presentat	ion of ext	ra clai	ms.		ı
Any p	atent applicati	on processing f	ees under 37	CFR 1.17.				

The issue fee set in 37 CFR 1.18 at or before mailing of the Notice

Form PTO-FB-A510 (10-85) (also form PTO-1082)

of Allowance, pursuant to 37 CFR 1.18 at or bef

// (\*\*\* | 7 0 0 = date Patent and Trademark Office - U.S. DEPARTMENT of COMMERCE

/ERIFIED STATEME (37 CFR 1.9(f) & 1	NT CLAIMING SM. 27(b))INDEPENDI	ALL ENTITY STATENT INVENTOR	rus	Docket Number (Optional)
Applicant or Patentee:	210m MASI	71		
Serial or Patent No.:				
Filed or Issued:				
Title: SYSTEM	and Welling	MUNICATIO	1 S	
As a below named inventor purposes of paying reduced	, I hereby declare that I qualifies to the Patent and Trac	alify as an independent in demark Office described	iventor as di in:	efined in 37 CFR 1.9(c) for
•	d herewith with title as list	ed above.		
the application ident	ified above.			
the patent identified				
I have not assigned, granted convey or license, any righ CFR 1.9(c) if that person h concern under 37 CFR 1.90	ts in the invention to any pead made the invention, or t	erson who would not quato any concern which wou	ury as an in ud not quali	dependent urvenior unicer 37
Each person, concern or or uon under contract or law to	ganization to which I have o assign, grant, convey, or	assigned, granted, conver license any rights in the i	yed, or licer invention is	nsed or am under an obliga- listed below:
No such person, o	oncern, or organization ex-	sts.		
Each such person	, concern or organization is	listed below		
710× 41	MMO) ABLA	NUNICATI	or 5	CTO
tion averring to their status	as small entities. (37 CFR	1.27)		n having rights to the inven-
I acknowledge the duty to enutlement to small enuty nance fee due after the date	status prior to paying, or a c on which status as a smal	the time of paying, the election is no longer appropriately is no longer appropriately.	ppriate. (37	CFR 1.28(b))
tion and belief are believed statements and the like so United States Code, and the	i to be true; and further that made are punishable by fin at such willful false statem	e or imprisonment, or bo- ents may joopardize the	th, under se	I statements made on informa- le knowledge that willful false ction 1001 of Title 18 of the the application, any patent
issuing thereon, or any pat			× 1	١
NAME OF INVENTOR	) NAME OF IN	TENTOR 1	NAME OF IN	VENTOR
NAME OF BITTERTOR	100 20 20			

Signature of inventor

Date

Signature of streetsor

Daco

Signature of inventor

VERIFIED STATEMENT CLAIMING SMALL ENTITY STATUS (37 CFR 1.9(f) & 1.27(c))-SMALL BUSINESS CONCERN	Docket Number (Optional)
Applicant or Patentee: 210N 1100AU  Serial or Patent No.:  Filed or Issued:  Title: 5757 FM GNO METHOD FOR COLUMN COMMUNICATION	MUDTIONS
I hereby declare that I am  the owner of the small business concern identified below:  an official of the small business concern empowered to act on behalf of the concern identified	
NAME OF SMALL BUSINESS CONCERN 71°N HADAW COM MUNICE ADDRESS OF SMALL BUSINESS CONCERN 48 HADEMOGIFT ST. R.	SHON COLION,
I hereby declare that the above identified small business concern qualifies as a small business con- and reproduced in 37 CFR 1.9(d), for purposes of paying reduced fees to the United States Patent and Tr of employees of the concern, including those of its affiliates, does not exceed 500 persons. For purpose of employees of the business concern is the average over the previous fiscal year of the concern of the part-time or temporary basis during each of the pay periods of the fiscal year, and (2) concerns are at directly or indirectly, one concern controls or has the power to control the other, or a third party or parties both.	ademark Office, in that the number is of this statement, (1) the number is persons employed on a full-time, filliates of each other when either, controls or has the power to control
I hereby declare that rights under contract or law have been conveyed to and remain with the smal with regard to the invention described in:	business concern identified above
the specification filed herewith with title as listed above. the application identified above. the patent identified above.	
If the rights held by the above identified small business concern are not exclusive, each individual rights in the invention must file separate verified statements averting to their status as small entities, and by any person, other than the inventor, who would not qualify as an independent inventor under 37 invention, or by any concern which would not qualify as a small business concern under 37 CFR 1.9(d) 37 CFR 1.9(e).	CFR 1.9(c) if that person made the
Each person, concern or organization having any rights in the invention is listed below:  The no such person, concern, or organization exists.  each such person, concern or organization is listed below.	
Separate verified statements are required from each named person, concern or organization hav to their status as small entities. (37 CFR 1.27)	ing rights to the invention averting
I acknowledge the duty to file, in this application or patent, notification of any change in status resentity status prior to paying, or at the time of paying, the earliest of the Issue fee or any maintenance fe as a small entity is no longer appropriate. (37 CFR 1.28(b))	ulting in loss of entitlement to small e due after the date on which status
I hereby declare that all statements made herein of my own knowledge are true and that all statements are believed to be true; and further that these statements were made with the knowledge that willful faster punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United State statements may jooperdize the validity of the application, any patent issuing thereon, or say patent directed.	s Code, and that such willful false
NAME OF PERSON SIGNING 7 (OR HADAD)	
TITLE OF PERSON IF OTHER THAN OWNER	n 150 m 150 d
ADDRESS OF PERSON SIGNING 48 MATCH MOGIA 57, PISHON SIGNATURE DATE JULY	(10)
SIGNATURE DATE DATE	10,000

## System and Method for Cellular Communications

#### Field of the Invention

The present invention relates to cellular and xDSL communication systems. More particularly, the invention relates to methods and systems for allocating subcarriers to subscribers in such a manner as to reduce the interference between users in the same cell and in adjacent cells or sectors.

#### Background of the Invention

At present, a cellular system may use a multicarrier system. Such systems are known in the art, and may comply with the DVB-T standards in Europe, or MMDS (Multichannel Multipoint Distribution Service) in U.S.A. These systems use the Orthogonal Frequency Division Multiplexing (OFDM) method, wherein symbols are transmitted in parallel by modulating a large number of orthogonal subcarriers.

A base station may be allocated, for example, 1700 out of 2000 subcarriers. The subcarriers may span a given frequency range, while being equidistantly located in the frequency domain.

The problem is how to allocate the various subcarriers to subscribers so as to minimize interference between users.

To illustrate such a problem: a base station is allocated, for example, a frequency range comprising 1600 subcarriers, divided into 64 groups of 25 subcarriers each.

A first user is allocated a spectrum comprising a plurality of subcarriers, one in each of the 64 groups.

A second user is allocated a spectrum comprising a plurality of subcarriers, a different one in each of the 64 groups.

Preferably, all the subcarriers allocated to the second user are different than those allocated to the first user.

Additional users are allocated other subcarriers.

One problem in the abovedetailed scheme is a possible collision between users, when two users are allocated the same subcarrier.

Such collisions are undesirable, as they may generate errors in communication, which may possibly increase the Bit Error Rate (BER) or slow down the communication channel.

Collisions may even occur if users are allocated different subcarriers. Thus, if there is a frequency deviation in the transmission of a first user and there are some subcarriers of that user which are close in frequency to some subcarriers of another user, then collisions may occur.

A collision occurs as the spectrum of that first user slides in frequency, to partially overlap with the spectrum of the second user.

Such frequency deviations may occur, for example, when one of the users is in motion, because of the Doppler effect.

The need for the use of smart subcarrier allocation may come from the frequency deviation that a user can suffer and its effect on other users. Allocating to users with all of their carriers allocated one adjunct to the other can cause, in a frequency deviation scenario a destruction of the deviated user and the adjunct one.

As the number of colliding subcarriers increases, the undesired disruption is more detrimental to communications.

Therefore, there is a problem of subcarriers allocation to users so as to reduce this undesirable effect.

The problem is further complicated in a multiuser cellular system, where there is a plurality of users communicating to a base station.

Each user is allocated a plurality of subcarriers, some of which may possibly be close in frequency to other user's subcarriers.

This is a complex, multidimensional problem that may be difficult to solve.

The above description relates to communications between one base station and users in that cell.

In real life, the problem is further aggravated because of interference between adjacent cells. Thus, a base station in one cell may receive interfering signals (subcarriers) from users in a nearby cell.

It is an objective of the present invention to address the problems of the allocation of subcarriers in a multicarrier cellular system.

#### Summary of the Invention

According to the present invention, there is provided a system and method for allocating subcarriers to users in a multicarrier cellular communication system and xDSL systems. It includes the use of special permutation series for carrier allocation.

According to one aspect of the invention, the subcarriers in each cell are allocated according to a Reed-Solomon (R-S) sequence. Each user in that cell is assigned a cyclic shifted version of a specific RS code sequence. This allocation decreases the number of subcarriers which are close to each other, for the various users in that cell.

Two users may use a maximum of one case where two subcarriers are adjacent to each other.

Thus, a method and system for allocating subcarriers in a cell is disclosed.

According to another aspect of the invention, users in adjacent cells are allocated different R-S codes, or the same code where we are adding one to the index of each code.

This approach may be used to minimize interference in one base station from users in another cell.

The use of R-S codes to frequency hopping in FH-CDMA is known in the art, as are known the low crosscorrelation properties of these codes. Until now, however, R-S codes have not been used for a group of subcarriers allocation in multicarriers systems.

According to yet another aspect of the invention, a distinction is made between the various users as to their interfering potential to a nearby cell, according to their distance from their own base station and their sectorial location.

An improved subcarrier allocation method that takes these effects into account is disclosed.

The present innovation may thus improve the reuse factor as well.

Thus, the invention relates to improvements in cellular and xDSL communication systems. These improvements include methods and systems for allocating subcarriers to subscribers in such a manner as to reduce the interference between users in the same cell and in adjacent cells or sectors.

Furthermore, the novel system and method will reduce the phase noise and interference due to the Doppler effect to neighbor users who have been allocated other subcarriers.

Further objects, advantages and other features of the present invention will become obvious to those skilled in the art upon reading the disclosure set forth hereinafter.

#### Brief Description of the Drawings

The invention will now be described by way of example and with reference to the accompanying drawings in which:

Fig. 1 illustrates a cellular wireless system.

Fig. 2 details a cellular transmitter/receiver including subcarriers allocation means.

Fig. 3 details a basic Reed-Solomon sequence of base 23 usable in subcarriers allocation.

Fig. 4 illustrates subcarrier allocation using Reed-Solomon sequences.

Fig. 5 details a method for subcarriers allocation to users in a cellular system.

Fig. 6 details another method for subcarriers allocation to users in a cellular system.

Fig. 7 further illustrates permutations used in subcarriers allocation, based on a Reed-Solomon (R-S) code.

# Detailed Description of the Preferred Embodiments

A preferred embodiment of the present invention will now be described by way of example and with reference to the accompanying drawings.

Fig. 1 illustrates a cellular wireless system with a plurality of wireless cells 11, 12 and 13 as illustrated, and a corresponding base station 111, 121, 131 in each cell.

In each cell there may be, at any given moment, a plurality of subscribers like the mobile subscribers 122, 123 and 124 in cell 12.

According to the present invention, there is made a distinction between subscribers close to a base station and subscribers closer to the periphery of a cell. The illustrated inner circle 126 separates between close subscribers like subscriber 124 which is located within circle 126, and more distant subscribers like 122 and 123 which are located within the outer ring 127.

The close subscribers transmit at a lower power, since they are close to the base station and need not transmit a high power. Therefore, close subscribers will interfere less with another base station, than distant subscribers. For example, subscriber 122 which is more distant from base 121, will interfere more with base 111 than the closely located subscriber 124.

Accordingly, a distant subscriber like subscribers 122 and 123 may be assigned different codes than close subscribers, to achieve a better separation from the codes used in adjacent cells.

A method for achieving better separation between users in a cellular system, using this effect, is further detailed with reference to Figs. 5 and 6.

The above system and method may achieve less interference between users in the cellular system, thus increasing the number of users who may be concurrently serviced in the system.

Where directional information is available in the base station, it is possible to further reduce interference between users and base stations.

The novel system and method uses a novel approach of directional code assignment, which is based on the discovery that subscribers in different sectors cause a different amount of interference to adjacent base stations.

For example, there is definitely a different amount of interference to base station 111 from subscribers in sectors 138 and 139 in cell 13.

A mobile subscriber 132 in sector 138 will cause a strong interference, whereas a mobile subscriber 133 will cause a weaker interference. The reason is wave propagation phenomena, wherein the intensity of the radio waves decreases as the fourth power of range, for transmitters and receivers close to ground.

Therefore, base station 131 may allocate different codes to subscribers in cell 13, taking into account possible interference to adjacent cells. Subscriber 132 will be assigned a code that is more farther away from that in base station 111, to counter the stronger interference caused by that subscriber, because of its closer distance.

Subscriber 133, however, may be assigned a code that is closer to the codes in base 111, since the much larger distance (about 2 to 3 times larger) will cause a decrease of 14 to 27 times in the power of interference to that base station.

Base station 131 is illustrated as having six sectors. A different number of sectors may be used. In any case, there is information available in the base station regarding the direction of each subscriber.

According to the invention, this information is used to allocate subcarriers to each subscriber, so as to minimize the interference between the subscribers and the base stations in the cellular system.

Such a smart subcarrier allocation will decrease interference in the system and will thus allow more users to operate in the allocated frequency band.

Fig. 2 details a cellular transmitter/receiver including subcarriers allocation means. The system may be used in a cellular multicarrier system, wherein subcarrier groups are allocated to each transmitter/receiver according to the methods detailed in the present disclosure.

The transmitter may include a transmit data in (serial) 211 being applied to a serial to parallel converter 212, which convert the data to parallel words. A subcarrier modulation unit 213 modulates the subcarriers allocated to the transmitter responsive to the data in 211.

A subcarriers allocation controller 22 allocates the subcarriers to be used in unit 213, out of the set of allocated subcarriers for that base station.

The Inverse Fast Fourier Transform (IFFT) unit 214 transforms the modulated subcarriers into the time domain, for transmission.

The IFFT unit is just one embodiment of a multicarrier modulation unit; other implementations of the unit are possible as well.

Since the time samples are concurrently being output out of unit 214, a parallel to serial converter 215 is used to transform the samples to serial form for transmission. The resulting signal is output as the transmit data out (serial) 216.

The receiver may include a receive data in (serial) 231 being applied to a serial to parallel converter 232, for the subsequent signal processing.

A Fast Fourier Transform (FFT) unit 233 converts the received signals into the frequency domain. A subcarrier demodulation unit 234 uses information regarding subcarriers in the received signal received from the subcarriers allocation controller 22 to demodulate the received signal.

A parallel to serial converter 235 reconstructs the received signal in the time domain, this being the receive data out (serial) 236.

Fig. 3 details a basic Reed-Solomon (R-S) code 23 based, usable in subcarriers allocation.

These codes have the maximal distance between shifted versions thereof, and accordingly are advantageously used in the present invention in a multicarrier cellular system to minimize collisions between subcarriers.

There are 23 cyclic rotations, from user to user.

Each row in the table corresponds to one cell or sector. Thus, for example, the first row may correspond to Cell 233/sector #1, the second row may correspond to Cell 233/sector #2, etc.

Fig. 4 illustrates an example of subcarrier allocation using Reed-Solomon codes. The method may be used to allocate subcarriers in a multcarrier system such as OFDM, filtered multitone (FMT), discrete multitone (DMT), etc.

Assuming a spectrum of available subcarriers 31 comprising subcarriers number 0, 1, 2, 3, 4, ... N, the subcarrier allocation first user 32 may be as illustrated. The value points to the allocated carrier within each group of subcarriers and its index is the sub-group numbering.

The subcarrier allocation for a second user 33 may be as illustrated, that is a shifted version of that for the first user 32.

It can be seen that adjacent subcarriers are separated by more than one step difference, except between subcarriers 16 and 17 in zone 323.

Similarly, there is the subcarrier allocation for a third user 34, as illustrated. Again, good separation between subcarriers is achieved, except one step difference in zone 334.

The Reed-Solomon series works on a prime number and generates all the numbers to this prime in a special permutation. The series has the special property that every cyclic permutation of the series gives the same result, and between any to cyclic permutation only 2 numbers are adjunct.

Therefore, if users are allocated carriers with groups of prime numbers, using the Reed- Solomon series for their carrier allocation within each carrier group, two users will have only one adjunct carrier to other users. If a user suffers from a frequency deviation, then only one subcarrier of all users is damaged, and an error correction code (ECC) scheme can handle it.

The next series is a Reed-Solomon series from the prime number of 23: 0,5,2,10,4,20,8,17,16,11,9,22,18,21,13,19,3,15,6,7,12,14,1

After two cyclic permutations we get: 2,10,4,20,8,17,16,11,9,22,18,21,13,19,3,15,6,7,12,14,1,0,5

For this cyclic permutation we see that for a group were the 22 carrier is allocated to one user another users will be allocated the 21 carrier, and only those two will be adjunct for all the carrier allocations.

The carrier allocations are done with groups of carriers containing the amount of prime number carriers. This scheme of allocation can mitigate the effect of one frequency deviated user (it may also be mobile), and therefore we may consider less modes of operation, and a simplified system.

Another advantage for this carrier allocation is derived from the frequency reuse that could be achieved. By using a different derived basic allocation we can allocate carriers in a different cell that uses the same frequency in such a way that the cross correlation of the allocation will be minimal. Therefore average the interference from that cell, this technique will enable to better deal with Co-Channel Interference (CCI) and help in the frequency reuse.

### Subcarriers allocation method

An example of subcarriers allocation using RS codes may include:

- A. all usable subcarriers are divided into 23 carrier groups, called basic groups. According to implementation, a different number of basic groups may be used.
- B. each group contains 23 carriers.
- C. a first user is assigned carriers in the above groups, as follows 12 ... in group No. 22 ... Subcarrier No.
- D. a second user is assigned carriers in the above groups, as follows 12 ... in group No. 18 ... Subcarrier No.
- E. a second user is assigned carriers in the above groups, as follows 12 ... in group No. 21 ... 17 16 Subcarrier No.
- F. subsequent users will be assigned subcarriers according to the same method as illustrated above.

One will recognize that the first user received one permutation of RS code, spread over the various groups of subcarriers.

The second user received the same sequence, shifted one location. The third user received the sequence shifted two places, etc.

The number of groups and the number of subcarriers in each group may vary, according to the number of subcarriers available.

For example, if more subcarriers are available, they may be further divided into three super-groups. Such a scheme will accommodate 3\*23\*23 subcarriers.

Additional details are presented with reference to Fig. 7 .

The above method may be used with the various systems and methods detailed in the present disclosure.

The subcarriers allocation is dynamic, as users enter or leave cells and a controller allocates subcarriers and cancels previous allocations that are no longer in use.

Fig. 5 details a method for subcarriers allocation in a cellular system, usable in a cellular system by the network manager, to allocate subcarriers to the various base stations, as follows:

Task 400: keeps a table of R-S codes for frequency group allocation to base stations

Task 405: assigns one set of subcarriers based on R-S codes to a base station

Task 410: assigns other sets of subcarriers based on R-S codes to other base stations in such a way that adjacent base stations have different R-S codes, to minimize the number of collision points therebetween.

In an OFDM system having N subcarriers available, numbered 0 to N-1, a first base station will be assigned subcarriers Fa, Fb, Fc ... where a, b, c... are members of an R-S code.

For example:

0, 5, 2, 10, 4, 20, 8, 17, 16, 11, 9, 22, 18, 21, 13, 19, 3, 15, 6,

where the above numbers refer to the abovedetailed subcarriers 0 to N-1.

An adjacent base station will be assigned a different R-S code, for example:

8, 5, 13, 7, 0, 11, 20, 19, 14, 12, 2, 21, 1

Task 415: where a base station has sectored coverage, a plurality of codes is assigned to that station for use with the various sectors. End of method.

Fig. 6 details another method for subcarriers allocation to users in a base station in a cellular system, as follows:

Task 440: base station keeps a table of available codes, wherein part of the codes are tagged "free" whereas the others are "in use"

Task 445: when a new subscriber gains access through a base station, he is assigned one of the codes for that cell.

For example, the code may include the subcarriers numbered:

0, 5, 2, 10, 4, 20, 8, 17, 16, 11, 9, 22, 18, 21, 13, 19, 3, 15, 6, ...

That code is tagged "in use" or "occupied" in the base station, to prevent its double assignment. Thus, each subscriber in a cell will receive a unique code from the base station.

If several sectors are used, the same code may be assigned to several subscribers, each in a different sector.

Task 450: when a subscriber leaves the cell, his R-S code is tagged as "free".

Task 455: a new subscriber is assigned a shifted version of the code

Task 460: different codes are allocated in various sectors, and taking into account the code of the nearby cell.

Task 465: optional: several codes are allocated to each station for near/far subscribers. Separating far/near subscribers using different codes achieves better separation from adjacent cells.

End of method.

Fig. 7 further illustrates the permutations used in subcarriers allocation. The carriers are based on a Reed-Solomon (R-S) code 23 based, as detailed in Fig. 3 above.

The usable carriers are divided into 23 carrier groups named "basic groups". Each group contains 23 basic groups.

There are three main groups, as illustrated.

These codes have the maximal distance between shifted versions thereof, and accordingly are advantageously used in the present invention in a multicarrier cellular system to minimize collisions between subcarriers.

There are 23 cyclic rotations, from user to user.

The three main groups are indicated in white, hashed and gray rectangles, respectively. Within each group, Reed-Solomon (R-S) codes are used.

It will be recognized that the foregoing is but one example of an apparatus and method within the scope of the present invention and that various modifications will occur to those skilled in the art upon reading the disclosure set forth hereinbefore.

#### Claims

What is claimed is:

- 1. In a multicarrier transceiver, a system for allocating subcarriers to subscribers, comprising a subcarriers allocation controller, connected to a subcarrier modulation unit in a transmitter and to a subcarrier demodulation unit in a receiver for setting a group of subcarriers to be used therein, wherein the transmitter and the receiver are part of the transceiver and wherein the subcarriers allocation is made according to a Reed-Solomon code.
- 2. The systems for allocating subcarriers to subscribers according to claim 1, wherein the transceiver is a wireless cellular device.
- 3. The systems for allocating subcarriers to subscribers according to claim 1, wherein the transceiver is a xDSL cellular device.
- 4. A systems for allocating subcarriers to subscribers, comprising:
  - A. a serial to parallel converter for the serial transmit data;
  - B. a subcarrier modulation unit connected to said converter;
  - C. a subcarriers allocation controller connected to the modulation unit;
  - D. a multicarrier modulation unit; and
- E. a parallel to serial converter, which generates the transmit data out (serial).
- 5. The systems for allocating subcarriers to subscribers according to claim 4, wherein the subcarriers allocation controller allocates subcarriers using a Reed-Solomon (R-S) codes scheme.
- 6. The systems for allocating subcarriers to subscribers according to claim 4, wherein the subcarriers allocation controller allocates subcarriers using, for each subscriber, a shifted version of a Reed-Solomon (R-S) code.

- 7. The systems for allocating subcarriers to subscribers according to claim 5, wherein the subcarriers allocation controller allocates subcarriers using, for adjacent subscribers, a shifted version of a Reed-Solomon (R-S) code that are separated by more than one step difference.
- 8. The systems for allocating subcarriers to subscribers according to claim 5, using a group of 22 carriers is allocated to one user, another user will be allocated a cycled version of the group.
- 9. In a multicarrier system, a method for allocating subcarriers to subscribers, comprising the steps of:
- A. keep a table of R-S codes for frequency group allocation to base stations;
- B. assign one set of subcarriers based on R-S codes to a base station;
- C. assign other sets of subcarriers based on R-S codes to other base stations in such a way that adjacent base stations have different R-S codes, to minimize the number of collision points therebetween.
- 10. The method for allocating subcarriers to subscribers according to claim 9, wherein in the multicarrier system having N subcarriers available, numbered 0 to N-1, a first base station will be assigned subcarriers Fa, Fb, Fc ... wherein a, b, c... are members of an R-S code.
- 11. The method for allocating subcarriers to subscribers according to claim 9, further including the step of:
- D. where a base station has sectored coverage, a plurality of codes are assigned to that station for use with the various sectors.

- 12. The method for allocating subcarriers to subscribers according to claim 9, further including the steps of:
- E. base station keeps a table of available codes, wherein part of the codes are tagged "free" whereas the others are "in use";
- F. when a new subscriber gains access through a base station, the subscriber is assigned one or more of the codes for that cell;
- G. when a subscriber leaves the cell, his R-S code is tagged as "free";
  - H. a new subscriber is assigned a shifted version of the code;
- I. different codes are allocated in various sectors, and taking into account the code of the nearby cell.
- 13. The method for allocating subcarriers to subscribers according to claim 12, further including the step of allocating several codes to each station for near/far subscribers, and separating far/near subscribers using different codes.
- 14. The method for allocating subcarriers to subscribers according to claim 12, further including the step of allocating several codes to each of several adjacent users within one cell, to decrease the interference resulting from Doppler, phase noise or collissions with other subscribers.
- 15. The method for allocating subcarriers to subscribers according to claim 12, wherein the code includes the subcarriers numbered:
  - 0, 5, 2, 10, 4, 20, 8, 17, 16, 11, 9, 22, 18, 21, 13, 19, 3, 15, 6.

#### Abstract of the Disclosure

A a system for allocating subcarriers to subscribers, comprising a subcarriers allocation controller, connected to a subcarrier modulation unit in a transmitter and to a subcarrier demodulation unit in a receiver for setting a group of subcarriers to be used therein. The transmitter and the receiver are part of the transceiver and subcarriers allocation is made according to a Reed-Solomon code. In a multicarrier system, a method for allocating subcarriers to subscribers, comprising the steps of:

A. keep a table of R-S codes for frequency group allocation to base stations; B. assign one set of subcarriers based on R-S codes to a base station; C. assign other sets of subcarriers based on R-S codes to other base stations in such a way that adjacent base stations have different R-S codes, to minimize the number of collision points therebetween.




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7

Post Office Address

	P10/58/01	( <b>6</b> -95)
Approved for use through	06/30/96, OMB 065	1-000
and Tradomack Office: IIS DEPAS	DTMENT OF COM	1000


Docket Number (Optional) DECLARATION FOR PATENT APPLICATION As a below named inventor. I hereby declare that: My residence, post office address and citizenship are as stated below next to my name. I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled SYSTEM AM ITETICAL COLOR (CAPINE COLOR ), the specification of \_\_\_, the specification of which is attached hereto unless the following box is checked: \_ as United States Application Number or PCT International Application was filed on and was amended on \_\_\_\_\_ I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above. I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR § 1.56. I hereby claim foreign priority benefits under 35 U.S.C. § 119(a)-(d) or § 365(b) of any foreign application(s) for paterit of inventor's certificate, or § 365(a) of any PCT international application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed. Priority Not Claimed Prior Foreign Application(s) (Day/Month/Year Filed) (Number) (Country) (Number) (Country) (Day/Month/Year Filed) I hereby claim the benefit under 35 U.S.C. § 119(e) of any United States provisional application(s) listed below (Application Number) (Filing Date) (Filing Date) (Application Number) I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s), or § 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR § 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application. (Application Number) (Status · patented, pending, abundaned) (Filing Date) (Application Number) (Status -- patented, pending, abandoned) (Filing Date) I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith at telephone number 0/193(3957-8550 Address all telephone calls to Address all correspondence to MARCHOGIAST, PISHON LEZION, ISPART I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon. I declare (or certify, verify or state) under penalty of perjury under the laws of the United States of America that the foregoing is true and correct. Full name of sole or first inventor (given name, family name) -Date \_ TO HOUR TO SCONG IS ROLL Full name of second joint inventor, if any (given name, family name) Second Inventor's signature Date Residence \_ Citizenship

Patent

Burden Hour Statement: This form is estimated to take .4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Office of Assistance Quality and Enhancement Division Patent and Trademark Office, Washington, DC 20231, and to the Office of Information and Regulatory Affairs, Office of Management and Budget (Project 0651-0032), Washington, DC 20231, and to the Office of Research Commissioner for Patents, Washington, DC 20231.

Additional inventors are being named on separately numbered sheets attached hereto

# United States Patent & Trademark Office Office of Initial Patent Examination -- Scanning Division



Application deficien	cies were four	nd during scanning:	
Page(s)	of		were not presen
for scanning.		(Document title)	
Page(s)	of		were not present
for scanning.		(Document title)	

Scanned copy is best available. Transmutal, Small entity
Declaration